

DARFON

小型で、優れた耐衝撃性と放熱性を備えています

NEW



サイズ 1608、2012

Darfon P/N	Nominal Inductance (μ H)	Inductance Tolerance [%]	DC Resistance Rdc [m Ω]		Heat Rating Current Idc (A)		Saturation Current Isat (A)		Marking
			Typ.	Max.	Typ.	Max.	Typ.	Max.	
SPM1608R22MPL8	0.22	$\pm 20\%$	33.0	40.0	3.40	3.00	5.50	5.00	—
SPM1608R24MPL8	0.24	$\pm 20\%$	34.0	41.0	3.30	2.90	5.30	4.80	—
SPM1608R47MPL8	0.47	$\pm 20\%$	80.0	100.0	2.60	2.30	4.10	3.70	—
SPM1608R56MPL8	0.56	$\pm 20\%$	85.0	110.0	2.20	1.90	4.00	3.50	—
SPM1608R68MPL8	0.68	$\pm 20\%$	110.0	130.0	2.10	1.90	3.30	3.00	—
SPM16081R0MPL8	1.0	$\pm 20\%$	180.0	200.0	2.10	1.80	3.00	2.60	—
SPM16082R2MPL8	2.2	$\pm 20\%$	220.0	260.0	1.40	1.20	1.50	1.30	—
SPM16084R7MPL8	4.7	$\pm 20\%$	585.0	700.0	1.00	0.80	1.20	1.00	—
SPM1608100MPL8	10.0	$\pm 20\%$	1450.0	1600.0	0.50	0.45	0.80	0.70	—

Darfon P/N	Nominal Inductance (μ H)	Inductance Tolerance [%]	DC Resistance Rdc [m Ω]		Heat Rating Current Idc (A)		Saturation Current Isat (A)		Marking
			Typ.	Max.	Typ.	Max.	Typ.	Max.	
SPM2012R24MPL8	0.24	$\pm 20\%$	18.0	23.0	6.5	5.9	6.5	6.0	—
SPM2012R33MPL8	0.33	$\pm 20\%$	33.0	45.0	4.3	4.0	5.2	4.8	—
SPM2012R47MPL8	0.47	$\pm 20\%$	34.0	50.0	3.5	3.3	5.0	4.6	—
SPM2012R68MPL8	0.68	$\pm 20\%$	50.0	60.0	3.7	3.3	4.2	3.7	—
SPM20121R0MPL8	1.0	$\pm 20\%$	55.0	70.0	3.3	2.9	4.0	3.5	—
SPM20121R5MPL8	1.5	$\pm 20\%$	118.0	135.0	2.2	1.9	3.0	2.5	—
SPM20122R2MPL8	2.2	$\pm 20\%$	160.0	185.0	2.2	1.8	2.6	2.3	—
SPM20123R3MPL8	3.3	$\pm 20\%$	253.0	300.0	1.8	1.5	1.9	1.6	—
SPM20124R7MPL8	4.7	$\pm 20\%$	285.0	325.0	1.7	1.5	1.6	1.4	—

DARFON製品は

『CoreStaff ONLINE』から
ご購入いただけます

ご購入はこちら ▶

corestaff
ONLINE